

Technical Data Sheet

93800052732_V02_en_GB

Voltage / Frequency

Cooling water temperature (in / out)

NOx emissions (dry, % O₂)

Mixture cooler 1st stage water temperature (in)

Mixture cooler 2nd stage water temperature (in)

Exhaust gas temperature

Catalytic converter

Special equipment

Elevation above sea level

Combustion air temperature

Relative combustion air humidity

Standard specifications and regulations

MTU 12V4000 GS

GG12V4000D1



V / Hz	400	/	50
°C		78 / 92	
mg/m ³ i.N.		< 250	
°C		60	
°C		417	
		not included	
m / mbar	100	/	1000
°C		35	
%		60	
		VDE-AR-N 4110	

Energy balance	%	100	75	50
Electrical Power ^{2) 3)}	kW	1521	1141	761
Energy input ^{4) 5)}	kW	3535	2705	1882
Thermal output total ⁶⁾	kW	881	641	438
Thermal output engine (block, lube oil, 1st stage mixture cooler) ⁶⁾	kW	881	641	438
Thermal output mixture cooler 1st stage ⁶⁾	kW			
Thermal output mixture cooler 2nd stage ⁶⁾	kW	81	51	28
Exhaust heat (120 °C) ⁶⁾	kW	(745)	(639)	(485)
Engine power ISO 3046-1 ²⁾	kW	1560	1171	784
Generator efficiency at power factor = 1	%	97.5	97.5	97.1
Electrical efficiency ⁴⁾	%	43.0	42.2	40.4
Total efficiency	%	89.0	89.5	89.5
Power consumption ⁷⁾	kW			

Combustion air / Exhaust gas

Combustion air volume flow ¹⁾	m ³ i.N./h	5943	4474	3050
Combustion air mass flow	kg/h	7675	5778	3939
Exhaust gas volume flow, wet ¹⁾	m ³ i.N./h	6241	4702	3208
Exhaust gas volume flow, dry ¹⁾	m ³ i.N./h	5586	4201	2860
Exhaust gas mass flow, wet	kg/h	7936	5977	4077
Exhaust temperature after turbocharger	°C	417	457	493

Reference fuel ⁸⁾

Natural gas			CH ₄ >95 Vol.%
Sewage gas			not applicable
Biogas			not applicable
Landfill gas			not applicable

Fuel requirements ⁹⁾

Minimum methane number	MN		80
Range of heating value: design / operation range without power derating	kWh/m ³ i.N.		10.0 - 10.5 / 8.5 - 11.0

Exhaust gas emissions ^{5) 8)} Compliance with emissions standards only for ≥ 761 kWel

NOx, stated as NO ₂ (dry, % O ₂)	mg/m ³ i.N.	< 250
CO (dry, % O ₂)	mg/m ³ i.N.	< 1000
HCHO (dry, % O ₂)	mg/m ³ i.N.	< 130
VOC (dry, % O ₂)	mg/m ³ i.N.	

Otto-gas engine, lean burn operation with turbocharging

Number of cylinders / configuration		12	/	V
Engine type			12V4000L64FNER	
Engine speed	1/min		1500	
Bore	mm		170.0	
Stroke	mm		210.0	
Displacement	dm ³		57.2	
Mean piston speed	m/s		10.5	
Compression ratio			12.5	
BMEP at nominal engine speed min-1	bar	21.8		
Lube oil consumption ¹⁰⁾	dm ³ /h	0.27		
Exhaust back pressure min. - max. after module	mbar - mbar		30 - 60	

Generator

Rating power (temperature rise class F) ¹¹⁾	kVA		2152
Insulation class / temperature rise class			H / F
Winding pitch			2/3
Protection			IP 23
Max. allowable p.f. inductive (overexcited) / capacitive (underexcited) ¹²⁾			0.8 / 0.95
Voltage tolerance / frequency tolerance	%		± 10 / ± 5

Engine cooling water system

Coolant temperature (in / out), design	°C		78 / 92
Coolant flow rate, constant ^{13) 14)}	m ³ /h		58.6
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m ³ /h	2.35 / 38.9
Max. operation pressure (coolant before engine)	bar		6.0

Exhaust gas heat exchanger (EGHE)

Exhaust gas temperature (out)	°C		
Coolant temperature (in / out), design	°C		
Coolant volumetric flow, constant ^{13) 14)}	m ³ /h		
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	kPa / m ³ /h	/
Min. coolant flow rate / min. operation gauge pressure	m ³ /h / bar		/
Max. operation pressure (coolant water)	bar		

Technical Data Sheet

93800052732_V02_en_GB

MTU 12V4000 GS

GG12V4000D1



Mixture cooler 1st stage, external				
Coolant temperature (in / out), design	°C			
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h			
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m³/h	/	
Min. coolant flow rate / min. operation gauge pressure	m³/h / bar		/	
Max. operation pressure before mixture cooler	bar			
Mixture cooling 2nd stage, external				
Coolant temperature (in / out), design	°C	60 / 62.1		
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h	35.3		
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m³/h	0.6	/ 46.7
Max. operation pressure before mixture cooler	bar		6	
Heating circuit interface				
Engine coolant temperature (in / out), design	°C			
Heating water temperature (in / out), design	°C			
Heating water flow rate, design ^{14) 16)}	m³/h			
Pressure drop, design ¹⁴⁾	Cv value ^{15) 16)}	bar / m³/h	/	
Max. operation gauge pressure (heating water)	bar			
Room ventilation				
Genset ventilation heat ¹⁷⁾	kW		88	
Inlet air temperature: (min./design/max.)	°C		30 / 35 / 40	
Min. engine room temperature ¹⁸⁾	°C		15	
Max. temperature difference ventilation air (in / out)	K		20	
Min. supply air volume flow rate (combustion + ventilation) ¹⁹⁾	m³ i.N./h		18500	
Gearbox	%	100	75	50
Efficiency	%	-	-	-
Starter battery				
Nominal voltage / power / capacity required	V / kW / Ah		24 / 9.0 / --	
Filling quantities				
Lube oil for engine	dm³		280	
Coolant in engine	dm³		200	
Coolant in mixture cooler	dm³		20	
Heating water for plate heat exchanger ²⁰⁾	dm³			
Lube oil for gearbox	dm³			
Gas regulation line				
Nominal size / gas pressure min. - max. (at gas regulation line inlet)	DN / mbar - mbar	80	/	155 - 250
Engine sound level ²¹⁾ (1 meter distance, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level				
Frequency	Hz	63	125	250 500
Sound pressure level	dB	83.3	87.4	88.6 91.3
Frequency	Hz	1000	2000	4000 8000
Sound pressure level	dB	90.1	87.3	92.9 103.9
Linear total sound pressure level	Lin dB	104.9		
A-weighted total sound pressure level	dB(A)	104.5		
A-weighted total sound power level	dB(A)	123.9		
Undampened exhaust noise ²¹⁾ (1 meter distance to outlet within 90°, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level				
Frequency	Hz	63	125	250 500
Sound pressure level	dB	118.5	120.3	110.8 102.2
Frequency	Hz	1000	2000	4000 8000
Sound pressure level	dB	92.9	92.3	92.1 82.5
Linear total sound pressure level	Lin dB	122.8		
A-weighted total sound pressure level	dB(A)	108.4		
A-weighted total sound power level	dB(A)	121.4		
Dimensions (aggregate)				
Length	mm		~ 5100	
Width	mm		~ 2000	
Height	mm		~ 2300	
Gross weight (dry weight)	kg		~ 13500 (~ 13000)	
Power derating				
Elevation			specific to the project	
Combustion air temperature			specific to the project	
Mixture cooler coolant temperature (in)			specific to the project	
Methane number			specific to the project	

Boundary conditions and consumables

Systems and consumables have to conform to the following actual company standards:

A001072

- Normal cubic meter at 1013 mbar and T = 273 K
- Prime power operation will be designed specific to the project
- Generator gross power at nominal voltage, power factor = 1 and nominal frequency
- According to ISO 3046 (+ 5 % tolerance), using reference fuel used at nominal voltage, power factor = 1 and nominal frequency
- Emission values during grid parallel operation
- Thermal output at layout temperature; tolerance +/- 8 %
- Power consumption of all electrical consumers which are mounted at the module / genset
- Deviations from the layout parameters respectively the reference fuel can have influence on the obtained efficiency and exhaust emissions
- Functional capability
- Reference value at nominal load (without amount of oil exchange)
- Generator (at nominal power) max. 1000 m height of location and max. 40 °C intake air temperature; else power derating
- Max. allowable cos phi at nominal power (view of producer)
- Stated values for cooling fluid composition 65% water and 35% glycol, adaption for use of other cooling fluid composition necessary
The system design must consider the tolerance.
- Pressure loss at reference flow rate
- The Cv value declares the volumetric flow in m³/h at a pressure drop of 1 bar. Min. and max. flow rate limits are defined.
- Stated values for pure water, adaption for other cooling fluid composition necessary
- Only generator- and surface losses
- Frost-free conditions must be guaranteed
- Amount of ventilation air must be adapted to the gas safety concept
- Assemblies including pipe work
- All sound pressure levels at nominal load, according to ISO 8528-10 and ISO 6798.
Resonance effects of the connected exhaust line can influence the exhaust noise sound pressure level
- Max. admissible cos phi depending on voltage in accordance with the requirements of the valid 'Standard specifications and regulations'