



TD_0062_L64_2542_50_250_EN_SI_V2

Voltage / Frequency
 Cooling water temperature (in / out)
 NOx emissions (dry, 5 % O₂)
 Mixture cooler 1st stage water temperature (in)
 Mixture cooler 2nd stage water temperature (in)
 Exhaust gas temperature
 Catalytic converter
 Special equipment
 Elevation above sea level
 Combustion air temperature
 Relative combustion air humidity
 Standard specifications and regulations

GG20V4000D1M

V / Hz
 °C
 mg/m³ i.N.
 °C
 °C
 °C
 m / mbar
 °C
 %

6300	/	50
	78 / 92	
	< 250	
	60	
	423	
	not included	
100	/	1000
	35	
	60	
VDE-AR-N 4110		

Energy balance	%	100	75	50
Electrical Power ²⁾³⁾	kW	2542	1906	1271
Energy input ⁴⁾⁵⁾	kW	5985	4561	3142
Thermal output total ⁶⁾	kW	2818	2202	1571
Thermal output engine (block, lube oil, 1st stage mixture cooler) ⁶⁾	kW	1512	1113	758
Thermal output mixture cooler 1st stage ⁶⁾	kW			
Thermal output mixture cooler 2nd stage ⁶⁾	kW	169	95	49
Exhaust heat optional (120 °C) ⁶⁾	kW	(1306)	(1089)	(813)
Engine power ISO 3046-1 ²⁾	kW	2600	1952	1307
Generator efficiency at power factor = 1	%	97.8	97.7	97.2
Electrical efficiency ⁴⁾	%	42.5	41.8	40.5
Total efficiency	%	89.6	90.1	90.5
Power consumption ⁷⁾	kW			
Combustion air / Exhaust gas				
Combustion air volume flow ¹⁾	m ³ i.N./h	10196	7609	5110
Combustion air mass flow	kg/h	13173	9830	6601
Exhaust gas volume flow, wet ¹⁾	m ³ i.N./h	10704	7996	5376
Exhaust gas volume flow, dry ¹⁾	m ³ i.N./h	9595	7151	4794
Exhaust gas mass flow, wet	kg/h	13612	10165	6831
Exhaust temperature after turbocharger	°C	423	457	493
Reference fuel⁸⁾				
Natural gas			CH ₄ >95 Vol.%	
Sewage gas			not applicable	
Biogas			not applicable	
Landfill gas			not applicable	
Fuel requirements⁹⁾				
Nominal rated methane number	MN		80	
Range of heating value: design / operation range without power derating	kWh/m ³ i.N.		10.0 - 10.5 / 8.0 - 11.0	
Exhaust gas emissions⁵⁾⁸⁾ Compliance with emissions standards only for ≥ 1271 kWel				
NOx, stated as NO ₂ (dry, 5 % O ₂)	mg/m ³ i.N.	< 250		
CO (dry, 5 % O ₂)	mg/m ³ i.N.	< 1000		
HCHO (dry, 5 % O ₂)	mg/m ³ i.N.	< 130		
VOC (dry, 5 % O ₂)	mg/m ³ i.N.			
Otto-gas engine, lean burn operation with turbocharging				
Number of cylinders / configuration		20	/	v
Engine type			20V4000L64FNER	
Engine speed	1/min		1500	
Bore	mm		170.0	
Stroke	mm		210.0	
Displacement	dm ³		95.33	
Mean piston speed	m/s		10.5	
Compression ratio			12.5	
BMEP at nominal engine speed min-1	bar	21.8		
Lube oil consumption ¹⁰⁾	dm ³ /h	0.45		
Exhaust back pressure min. - max. after module	mbar - mbar		30 - 60	
Generator				
Rating power (temperature rise class F) ¹¹⁾	kVA		3404	
Insulation class / temperature rise class			H / F	
Winding pitch			5/6	
Protection			IP 23	
Max. allowable p.f. inductive (overexcited) / capacitive (underexcited) ¹²⁾			0.8 / 0.95	
Voltage tolerance / frequency tolerance	%		± 10 / ± 5	
Engine cooling water system				
Coolant temperature (in / out), design	°C	78 / 92		
Coolant flow rate, constant ¹³⁾¹⁴⁾	m ³ /h	100.06		
Pressure drop, design ¹⁴⁾	Cv value ¹³⁾¹⁵⁾	3.3	/	56.5
Max. operation pressure (coolant before engine)	bar		6	
Exhaust gas heat exchanger (EGHE)				
Exhaust gas temperature (out)	°C			
Coolant temperature (in / out), design	°C			
Coolant volumetric flow, constant ¹³⁾¹⁴⁾	m ³ /h			
Pressure drop, design ¹⁴⁾	Cv value ¹³⁾¹⁵⁾		/	
Min. coolant flow rate / min. operation gauge pressure	m ³ /h / bar		/	
Max. operation pressure (coolant water)	bar			



TD_0062_L64_2542_50_250_EN_SI_V2

GG20V4000D1M

Mixture cooler 1st stage, external					
Coolant temperature (in / out), design	°C				
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h				
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m³/h		/	
Min. coolant flow rate / min. operation gauge pressure	m³/h / bar		/		
Max. operation pressure before mixture cooler	bar				
Mixture cooling 2nd stage, external					
Coolant temperature (in / out), design	°C		60 / 63.6		
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h		44.0		
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m³/h		/ 49.2	
Max. operation pressure before mixture cooler	bar		6		
Heating circuit interface					
Engine coolant temperature (in / out), design	°C				
Heating water temperature (in / out), design	°C				
Heating water flow rate, design ^{14) 16)}	m³/h				
Pressure drop, design ¹⁴⁾	Cv value ^{15) 16)}	bar / m³/h		/	
Max. operation gauge pressure (heating water)	bar				
Room ventilation					
Genset ventilation heat ¹⁷⁾	kW		136		
Inlet air temperature: (min./design/max.)	°C		30 / 35 / 40		
Min. engine room temperature ¹⁸⁾	°C		15		
Max. temperature difference ventilation air (in / out)	°C		20		
Min. supply air volume flow rate (combustion + ventilation) ¹⁹⁾	m³ i.N./h		29500		
Gearbox	%		100		75 50
Efficiency	%				
Starter battery					
Nominal voltage / power / capacity required	V / kW / Ah		24 / 2 x 9 / --		
Filling quantities					
First filling quantity lube oil / refilling amount lube oil	dm³		478 / 450		
Coolant in engine circuit	dm³		310		
Coolant in mixture cooler	dm³		25		
Heating water for plate heat exchanger ²⁰⁾	dm³				
Lube oil for gearbox	dm³				
Gas regulation line					
Nominal size / gas pressure min. - max. (at gas regulation line inlet)	DN / mbar - mbar		100		/ 172 - 250
Engine sound level²¹⁾ (1 meter distance, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level					
Frequency	Hz	63	125	250	500
Sound pressure level	dB	93.1	95.1	91.5	95.0
Frequency	Hz	1000	2000	4000	8000
Sound pressure level	dB	93.5	92.8	91.8	99.7
Linear total sound pressure level	Lin dB	104.0			
A-weighted total sound pressure level	dB(A)	102.0			
A-weighted total sound power level	dB(A)	122.3			
Undampened exhaust noise²¹⁾ (1 meter distance to outlet within 90°, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level					
Frequency	Hz	63	125	250	500
Sound pressure level	dB	118.4	118.9	108.8	100.5
Frequency	Hz	1000	2000	4000	8000
Sound pressure level	dB	91.9	91.5	91.8	84.1
Linear total sound pressure level	Lin dB	122.0			
A-weighted total sound pressure level	dB(A)	106.5			
A-weighted total sound power level	dB(A)	119.4			
Dimensions (aggregate)					
Length	mm		~ 6200		
Width	mm		~ 2400		
Height	mm		~ 2400		
Gross weight (dry weight)	kg		~ 20500 (~ 19500)		
Power derating					
Elevation	specific to the project				
Combustion air temperature	specific to the project				
Mixture cooler coolant temperature (in)	specific to the project				
Methane number	specific to the project				

Boundary conditions and consumables
 Systems and consumables have to conform to the following actual company standards: A001072

- 1) Normal cubic meter at 1013 mbar and T = 273 K
- 2) Prime power operation will be designed specific to the project
- 3) Generator gross power at nominal voltage, power factor = 1 and nominal frequency
- 4) According to ISO 3046 (+ 5 % tolerance), using reference fuel used at nominal voltage, power factor = 1 and nominal frequency
- 5) Emission values during grid parallel operation
- 6) Thermal output at layout temperature; tolerance +/- 8 %
- 7) Power consumption of all electrical consumers which are mounted at the module / genset
- 8) Deviations from the layout parameters respectively the reference fuel can have influence on the obtained efficiency and exhaust emissions
- 9) Functional capability
- 10) Reference value at nominal load (without amount of oil exchange) oil density set to 860g/l
- 11) Generator (at nominal power) max. 1000 m height of location and max. 40 °C intake air temperature; else power derating
- 12) Max. allowable cos phi at nominal power (view of producer)
- 13) Stated values for cooling fluid composition 65% water and 35% glycol, adaption for use of other cooling fluid composition necessary
 The system design must consider the tolerance.
- 14) Pressure loss at reference flow rate
- 15) The Cv value declares the volumetric flow in m³/h at a pressure drop of 1 bar. Min. and max. flow rate limits are defined.
- 16) Stated values for pure water, adaption for other cooling fluid composition necessary
- 17) Only generator- and surface losses
- 18) Frost-free conditions must be guaranteed
- 19) Amount of ventilation air must be adapted to the gas safety concept
- 20) Assemblies including pipe work
- 21) All sound pressure levels at nominal load, according to ISO 8528-10 and ISO 6798.
- 22) Max. admissible cos phi depending on voltage in accordance with the requirements of the valid 'Standard specifications and regulations'