



## Technical Data Sheet

## MTU 8V4000 GS

006260276\_260276\_Q01\_2\_8L64\_700\_50\_250\_EN\_SI\_V1

Voltage / Frequency

Cooling water temperature (in / out)

NOx emissions (dry, 5 % O<sub>2</sub>)

Mixture cooler 1st stage water temperature (in)

Mixture cooler 2nd stage water temperature (in)

Exhaust gas temperature

Catalytic converter

Special equipment

Elevation above sea level

Combustion air temperature

Relative combustion air humidity

Standard specifications and regulations

**GG08V4000D1**

V / Hz	400	/	50
°C		78 / 89	
mg/m <sup>3</sup> i.N.		< 250	
°C			
°C		56	
°C		450	
		not included	
m / mbar	100	/	1000
°C		35	
%		60	
		VDE-AR-N 4110	

**Energy balance**

	%	100	75	50
Electrical Power <sup>2) 3)</sup>	kW	700	525	347
Energy input <sup>4) 5)</sup>	kW	1709	1324	931
Thermal output total <sup>6)</sup>	kW	828	652	469
Thermal output engine (block, lube oil, 1st stage mixture cooler) <sup>6)</sup>	kW	431	330	236
Thermal output mixture cooler 1st stage <sup>6)</sup>	kW			
Thermal output mixture cooler 2nd stage <sup>6)</sup>	kW	34	23	14
Exhaust heat optional (120 °C) <sup>6)</sup>	kW	( 397 )	( 322 )	( 233 )
Engine power ISO 3046-1 <sup>2)</sup>	kW	722	545	364
Generator efficiency at power factor = 1	%	97.0	96.4	95.4
Electrical efficiency <sup>4)</sup>	%	41.0	39.6	37.3
Total efficiency	%	89.4	88.9	87.6
Power consumption <sup>7)</sup>	kW			

**Combustion air / Exhaust gas**

Combustion air volume flow <sup>1)</sup>	m <sup>3</sup> i.N./h	2830	2160	1490
Combustion air mass flow	kg/h	3656	2790	1927
Exhaust gas volume flow, wet <sup>1)</sup>	m <sup>3</sup> i.N./h	2975	2272	1570
Exhaust gas volume flow, dry <sup>1)</sup>	m <sup>3</sup> i.N./h	2658	2026	1397
Exhaust gas mass flow, wet	kg/h	3782	2888	1995
Exhaust temperature after turbocharger	°C	450	471	492

**Reference fuel <sup>8)</sup>**

Natural gas	CH <sub>4</sub> >95 Vol.%
Sewage gas	not applicable
Biogas	not applicable
Landfill gas	not applicable
Propane HD 5	not applicable

**Fuel requirements <sup>9)</sup>**

Nominal rated methane number	MN	70
Range of heating value: design / operation range without power derating	kWh/m <sup>3</sup> i.N.	10.0 - 10.5 / 8.0 - 11.0
<b>Exhaust gas emissions <sup>5) 6)</sup> Compliance with emissions standards only for ≥ 347 kWel</b>		
NOx, stated as NO <sub>2</sub> (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	< 250
CO (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	< 1200
HCHO (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	< 130
VOC (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	

**Otto-gas engine, lean burn operation with turbocharging**

Number of cylinders / configuration	8	/	v
Engine type		8V4000L64FNTR	
Engine speed	1/min	1500	
Bore	mm	170.0	
Stroke	mm	210.0	
Displacement	dm <sup>3</sup>	38.13	
Mean piston speed	m/s	10.5	
Compression ratio		12.5	
BMEP at nominal engine speed min-1	bar	15.1	
Lube oil consumption <sup>10)</sup>	dm <sup>3</sup> /h	0.18	
Exhaust back pressure min. - max. after module	mbar - mbar	30 - 60	

**Generator**

Rating power (temperature rise class F) <sup>11)</sup>	kVA	1625
Insulation class / temperature rise class	H / F	
Winding pitch	2/3	
Protection	IP 23	
Max. admissible cos phi inductive (overexcited) / capacitive (underexcited) <sup>12) 22)</sup>		0.8 / 0.95
Voltage tolerance / frequency tolerance	%	+/- 10 / +/- 5

**Engine cooling water system**

Coolant temperature (in / out), design	°C	78 / 89
Coolant flow rate, constant <sup>13) 14)</sup>	m <sup>3</sup> /h	40.0
Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	bar / m <sup>3</sup> /h
Max. operation pressure (coolant before engine)		2.3
	bar	6

**Exhaust gas heat exchanger (EGHE)**

Exhaust gas temperature (out)	°C	
Coolant temperature (in / out), design	°C	
Coolant volumetric flow, constant <sup>13) 14)</sup>	m <sup>3</sup> /h	
Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	kPa / m <sup>3</sup> /h
Min. coolant flow rate / min. operation gauge pressure		/
Max. operation pressure (coolant water)	bar	/



## Technical Data Sheet

## MTU 8V4000 GS

006260276\_260276\_Q01\_2\_8L64\_700\_50\_250\_EN\_SI\_V1

### GG08V4000D1

#### Mixture cooler 1st stage, external

Coolant temperature (in / out), design		°C		
Coolant volumetric flow, design, constant <sup>13) 14)</sup>		m³/h		
Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	bar / m³/h	/	
Min. coolant flow rate / min. operation gauge pressure		m³/h / bar	/	
Max. operation pressure before mixture cooler		bar		

#### Mixture cooler 2nd stage, external

Coolant temperature (in / out), design		°C	56 / 56.9	
Coolant volumetric flow, design, constant <sup>13) 14)</sup>		m³/h	39.0	
Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	bar / m³/h	0.73	/
Max. operation pressure before mixture cooler		bar		46.0

#### Heating circuit interface

Engine coolant temperature (in / out), design		°C		
Heating water temperature (in / out), design		°C		
Heating water flow rate, design <sup>14) 16)</sup>		m³/h		
Pressure drop, design <sup>14)</sup>	Cv value <sup>15) 16)</sup>	bar / m³/h	/	
Max. operation gauge pressure (heating water)		bar		

#### Room ventilation

Genset ventilation heat <sup>17)</sup>		kW	37	
Inlet air temperature: (min./design/max.)		°C	30 / 35 / 40	
Min. engine room temperature <sup>18)</sup>		°C	15	
Max. temperature difference ventilation air (in / out)		°C	20	
Min. supply air volume flow rate (combustion + ventilation) <sup>19)</sup>			8000	

#### Gearbox

Efficiency	%	100	75	
Starter battery	%			

Nominal voltage / power / capacity required

V / kW / Ah

24 / 9 / --

#### Filling quantities

First filling quantity lube oil / refilling amount lube oil		dm³	220 / 200	
Coolant in engine circuit		dm³	135	
Coolant in mixture cooler		dm³	15	
Heating water for plate heat exchanger <sup>20)</sup>		dm³		
Lube oil for gearbox		dm³		

#### Gas regulation line

Nominal size / gas pressure min. - max. (at gas regulation line inlet)		DN / mbar - mbar	80	/	107 - 250
<b>Engine sound level <sup>21)</sup> (1 meter distance, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level</b>					

Frequency	Hz	63	125	250	500
Sound pressure level	dB	79.3	89.1	90.0	92.6
Frequency	Hz	1000	2000	4000	8000
Sound pressure level	dB	92.2	89.2	88.8	100.0
Linear total sound pressure level	Lin dB	102.3			
A-weighted total sound pressure level	dB(A)	101.0			
A-weighted total sound power level	dB(A)	120.0			

#### Undampened exhaust noise <sup>21)</sup> (1 meter distance to outlet within 90°, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level

Frequency	Hz	63	125	250	500
Sound pressure level	dB	102.1	118.4	110.3	106.1
Frequency	Hz	1000	2000	4000	8000
Sound pressure level	dB	101.4	99.5	93.4	84.1
Linear total sound pressure level	Lin dB	119.4			
A-weighted total sound pressure level	dB(A)	109.0			
A-weighted total sound power level	dB(A)	121.5			

#### Dimensions (aggregate)

Length	mm		~ 4100	
Width	mm		~ 1900	
Height	mm		~ 2300	
Gross weight (dry weight)	kg		~ 12000 (~ 11500)	

#### Power derating

Maximum ambient air dew point on site	°C	26.0	
Configuration change		No	
Mixture cooler coolant temperature (in)		specific to the project	
Methane number		specific to the project	

#### Boundary conditions and consumables

Systems and consumables have to conform to the following actual company standards:

A001072

- 1) Normal cubic meter at 1013 mbar and T = 273 K
- 2) Prime power operation will be designed specific to the project
- 3) Generator gross power at nominal voltage, power factor = 1 and nominal frequency (ISO 8528-6)
- 4) According to ISO 3046 (+ 5 % tolerance), using reference fuel used at nominal voltage, power factor = 1 and nominal frequency
- 5) Emission values during grid parallel operation
- 6) Thermal output at layout temperature; tolerance +/- 8 %
- 7) Power consumption of all electrical consumers which are mounted at the module / genset
- 8) Deviations from the layout parameters respectively the reference fuel can have influence on the obtained efficiency and exhaust emissions
- 9) Functional capability
- 10) Reference value at nominal load (without amount of oil exchange) oil density set to 860g/l
- 11) Generator (at nominal power) max. 1000 m height of location and max. 40 °C intake air temperature; else power derating
- 12) Max. allowable cos phi at nominal power (view of producer)
- 13) Stated values for cooling fluid composition 65% water and 35% glycol, adaption for use of other cooling fluid composition necessary  
The system design must consider the tolerance.
- 14) Pressure loss at reference flow rate
- 15) The Cv value declares the volumetric flow in m³/h at a pressure drop of 1 bar. Min. and max. flow rate limits are defined.
- 16) Stated values for pure water, adaption for other cooling fluid composition necessary
- 17) Only generator- and surface losses
- 18) Frost-free conditions must be guaranteed
- 19) Amount of ventilation air must be adapted to the gas safety concept
- 20) Assemblies including pipe work
- 21) All sound pressure levels at nominal load, according to ISO 8528-10 and ISO 6798.
- 22) Max. admissible cos phi depending on voltage in accordance with the requirements of the valid 'Standard specifications and regulations'